

Item No.: 231.98.010

SAFE-O-TRONIC® access LS 200

Electronic PIN code locking system with RFID Programming and RFID Master key function. For lockers, safe-deposit boxes and functional furniture, with wear resistant capacitive key pad (touch-sensor). Rectangular lever operates the locking cam with many possibilities to individualize locker numbers, writing, or logo by exchangeable plates. Suitable for locker doors originally prepared for cylinder lever locks. Adapts to both right and left handed locker doors in four different directions. Lock is released after entering a 4 digit code; 99 different user codes including time limits per lock

- Free or fixed locker operation modes
- Adjustable for automatic allocation of sequence user codes for guests
- Set time zone for limited locking authorizations
- Set up for automatic opening or blocking in case the programmed time is exceeded
- Master key function to open and close
- Emergency opening (only opening) in case user code is forgotten
- RFID data medium for quick programming
- RFID data medium with Master Key – Function with limited locking authorizations for the entire locking system or specific areas within the system
- Audit trail for 500 operations
- Blocking time against unauthorized attempts to open
- Optional **Lock Manager LS 200 Software** (Item No. **231.98.600**) to program and administer the locking system with help of a **System Key Set** (Item No. **231.98.501**), and **USB Reader** (Item No. **231.98.510**)
- Optional **SAFE-O-TRONIC® LS 200 Programming Key Set** (Item No. **231.98.508**) to quickly program and operate lock with RFID data medium – No additional software required
- Manual feature to unlock for functional safety in case of jammed locker doors
- Convenient user guidance by Free/Occupied display as well as optical and acoustic signal
- Rectangular/comfort rotary knob for individuals with disabilities
- Battery operated; Battery is positioned outside of the locker door – no cabling required (Battery Item No. **231.98.210**)
- Intelligent battery management system ensures that the locker door opens at any time
- Battery life is approximately 3 years at 30 cycles per day
- Certified security against break-up
- Suitable for all kinds of door materials and wet areas; protected against spray water (IP 43)
- Award winning design
- Housing dimensions with rotary knob (W x D x H):
38 mm (1 1/2") x 33 mm (1 5/16") x 151 mm (5 15/16")
- Maximum door thickness of 19 mm (3/4") including mounting material



3901 Cheyenne Drive
P.O. Box 4000
Archdale, NC 27263
1-800-423-3531
www.hafele.com