



SLIDE MODEL	SLIDE LENGTH	TRAVEL	A	B	C	D	E	F
C 4520-12SCP	11.81[300.0]	10.83[275.0]	5.04[128.0]	----	----	----	3.78[96.0]	7.56[192.0]
C 4520-14SCP	13.78[350.0]	12.68[322.0]	6.30[160.0]	----	----	----	5.04[128.0]	7.95[202.0]
C 4520-16SCP	15.75[400.0]	14.37[365.0]	5.04[128.0]	8.82[224.0]	----	----	5.04[128.0]	10.71[272.0]
C 4520-18SCP	17.72[450.0]	16.54[420.0]	5.04[128.0]	8.82[224.0]	----	----	5.04[128.0]	12.60[320.0]
C 4520-20SCP	19.69[500.0]	18.90[480.0]	5.04[128.0]	8.82[224.0]	12.60[320.0]	----	6.30[160.0]	13.86[352.0]
C 4520-22SCP	21.65[550.0]	20.28[515.0]	5.04[128.0]	8.82[224.0]	13.86[352.0]	----	6.30[160.0]	15.12[384.0]
C 4520-24SCP	23.62[600.0]	22.64[575.0]	5.04[128.0]	8.82[224.0]	15.12[384.0]	----	7.56[192.0]	17.64[448.0]
C 4520-26SCP	25.59[650.0]	24.61[625.0]	5.04[128.0]	8.82[224.0]	15.12[384.0]	18.90[480.0]	8.82[224.0]	20.16[512.0]
C 4520-28SCP	27.56[700.0]	26.57[675.0]	5.04[128.0]	8.82[224.0]	15.12[384.0]	20.16[512.0]	8.82[224.0]	21.42[544.0]

- 1. HOLE NOT PRESENT ON 14" SLIDE. "F" DIMENSION MEASURED TO VERTICAL SLOT.
- 10. SLOT NOT PRESENT ON 14" SLIDE.
- 9. SLOTS NOT PRESENT ON 12" SLIDE.
- 8. SLIDE IS PROVIDED WITH A EASY CLOSE MECHANISM.
- 7. SLIDE IS PROVIDED WITH LEVER DISCONNECT.
- 6. SLIDE IS UNHAND.
- 5. HOLES OTHER THAN THOSE SHOWN MAY BE IN THE MEMBERS AT ACCURIDE OPTION.
- 4. FINISH: ELECTRO-ZINC PLATED.
- 3. LUBRICANT: HIGH-LOW TEMPERATURE GREASE.
- 2. BALL BEARINGS: CARBURIZED STEEL.
- 1. MATERIAL: SLIDE MEMBERS AND COMPONENT PARTS: WORK HARDENED COLD-ROLLED STEEL.

SYM.	IS	DESCRIPTION	WAS	DATE	APPD.
REVISIONS					

NOTES: UNLESS OTHERWISE SPECIFIED

PRODUCT COVERED BY U.S. PATENTS #3205025, #3778120 AND OTHER U.S. PATENTS PENDING.					
CUSTOMER:			REV. *		
P/N: C 4520-XXSC			REV. *		
SCALE	DATE	CONTROLLING DOCUMENT			
N.T.S.		<input checked="" type="checkbox"/> ACCURIDE <input type="checkbox"/> CUSTOMER			
DRAWN	J. SALAS	TOLERANCES NOT SHOWN			
APPROVED	12/17/2020	in .xxx ± .010 .25 mm .xx ± .030 .76 Travel ± .13 3.3 Holes ± .006 .15 Angular ± 1°			
		econoRunner		3 MEMBER SOFT CLOSE SLIDE	
		PART NUMBER		REV.	
		C 4520-XXSC		*	
THIS DOCUMENT IS FURNISHED FOR THE EXPRESS AND EXCLUSIVE PURPOSE OF CONVEYING INFORMATION TO CUSTOMERS AND SUPPLIERS OF ACCURIDE INTERNATIONAL INC., AND IS NOT TO BE DISCLOSED TO COMPETITIVE SOURCES.					